

3212 B

Pressure gauge with central needle

Desbordes

Technical Data Sheet



Description

Pressure gauge with central needle in ABS casing with axial connection and with a diameter 50 mm.



3212 B

Pressure gauge with central needle DESBORDES

PFA in bar	Ref.	Designation
4	149B7176	Pressure gauge
6	149B7177	Pressure gauge
10	149B7174	Pressure gauge
16	149B7175	Pressure gauge

Technical features

Operating temperature	-20 °C at +60 °C
Casing	ABS with axial connection
Connection	Male thread 1/4", horizontal
Face	Diameter 50 mm
Mediums	Water, air
Class	NC

The descriptions and photographs contained in this product specification sheet are supplied by way of information only and are not binding.

Socla reserves the right to carry out any technical and design improvements to its products without prior notice. Warranty : All sales and contracts for sale are expressly conditioned on the buyer's assent to Socla terms and conditions found on its website at www.socla.com. Socla hereby objects to any term, different from or additional to Socla terms, contained in any buyer communication in any form, unless agreed to in a writing signed by an officer of Socla.



A WATTS Brand

Socla sas

365 rue du Lieutenant Putier • 71530 Virey-Le-Grand • France

Tel. +33 03 85 97 42 00 • Fax +33 03 85 97 42 42

contact@wattswater.com • www.socla.com

ISO 9001 version 2015 / ISO 18001