

212 AD

Pressure gauge "PRESSADE"

Desbordes

Technical Data Sheet



Description

The Pressure gauge **PRESSADE** 212 AD is for quick inspection of pressure on any orifice from 8 to 20 mm .

- Rubber connection
- Exclusive patent
- Dial from 0 at 10 bar
- Under blister



212 AD

Pressure gauge "PRESSADE" DESBORDES

PFA in bar	Ref.	Designation
10	149B7145	Pressure gauge

Technical features

Maximum permissible pressure	10 bar - the 3 bar pressure is required by the acoustic standard.
Mediums	Water

The descriptions and photographs contained in this product specification sheet are supplied by way of information only and are not binding.

Socla reserves the right to carry out any technical and design improvements to its products without prior notice. Warranty : All sales and contracts for sale are expressly conditioned on the buyer's assent to Socla terms and conditions found on its website at www.socla.com. Socla hereby objects to any term, different from or additional to Socla terms, contained in any buyer communication in any form, unless agreed to in a writing signed by an officer of Socla.



A WATTS Brand

Socla sas

365 rue du Lieutenant Putier • 71530 Virey-Le-Grand • France

Tel. +33 03 85 97 42 00 • Fax +33 03 85 97 42 42

contact@wattswater.com • www.socla.com

ISO 9001 version 2015 / ISO 18001