

Technical data sheet

Type 251S

EA antipollution non-return valve

Applications and special features



- Operates in any position
- Minimum head loss
- Silent and robust
- Does not generate hammering
- Closing system : double axial guiding with return spring
- Excellent sealing at high as well as at low pressure ensured by a specially designed lip ring-seal.
- Drilled bosses 1/8" with brass plug

Technical description

C	DN	PFA (bar)	PS (bar)				Cat.	References	Vvs-nr
	mm		L1	L2	G1	G2			
15	1/2	10	10	10	10	10	3.3	1498 3511	

C : water meter


Important notice :

The indicated pressure for the different categories of fluids (L1/L2/G1/G2) is under no condition a guarantee of use. Therefore, it is essential to validate the use of products under given operating conditions.

- **Connection** : Female/Male BSP thread, with union nut
- **Permissible operating pressure PFA - water-** (for supply, distribution and disposal of water) : See table
- **Maximum permissible pressure PS - other mediums** : See tableau
- **θ** : Maxi. 80 °C
- **Mediums** : Clear liquids
- **Approvals** : ACS
- **International construction Standards** : NF Antipollution according to NF EN 13959
Thread connection according to NF E 03-005 ISO 228
NF EN1717

Overall dimensions


Connections A		B	C	D	E	Weight
C	mm	mm	mm	mm	mm	kg
15	3/4	58	30	22	18	0,16



Technical data sheet Type 251S - EA antipollution non-return valve

Spare parts list and materials

Nb	Description	Materials	EURO	ANSI
1	CASING	Brass	CuZn40Pb2	
2	GUIDE	POM (polyacetal)		
3	CLOSING SYSTEM	POM (polyacetal)		
4	SPRING	Stainless steel	X10CrNi18-8	AISI 302
5	SEAL	NBR		
6	PLUG	Brass	CuZn39Pb3	
7	SEAL	EPDM		
8	SEAT	POM (polyacetal)		
9	SEAL	EPDM		




Working principle

DN		Opening pressure (in mm WC)	Kv	ζ
C	"		m ³ /H	
15	1/2	between 50 and 200	4,7	3,7

Direction for use :

- Solid line : Valve completely open
- Dotted line : opening stage of valve



Socla can accept no responsibility for possible errors in catalogue, brochures and other printed material. Socla reserve the right to alter its products without notice. This also applies to products already agreed. All trademarks in this material are the property of the respective companies. All right reserved.

Socla SAS

365 rue du lieutenant Putier
 71530 VIREY LE GRAND
 Postal address : BP 10273
 71107 CHALON SUR SAONE Cedex

Tel : 33 3 85 97 42 52
 Fax : 33 3 85 97 97 42
<http://www.socla.com>
 e-mail: commer@socla.com